

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Detaflex 4000
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

DL CHEMICALS
Roterijstraat 201-203
B-8793 Waregem - Belgium
T + 32 56 62 70 51 - F + 32 56 60 95 68
info@dl-chem.com - www.dl-chem.com

1.4. Emergency telephone number

Emergency number : + 32 70 245 245

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation Not classified

Respiratory sensitisation, Category 1 H334

Skin sensitisation Not classified

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

CLP Signal word

: Danger

Hazardous ingredients

: Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; 4,4'-methylenediphenyl diisocyanate

Hazard statements (CLP)

: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements (CLP)

: P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

Unknown acute toxicity

: 36% of the mixture consists of components of unknown acute oral toxicity.
38% of the mixture consists of components of unknown acute dermal toxicity.

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium dioxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17	< 10	Not classified
reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0 (REACH-no) 01-2119488216-32	2,5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Hydrocarbons, C11-C14, n-alkanes, iso-alkanes, cyclic, <2% aromatic substance with a Community workplace exposure limit	(EC-No.) 926-141-6 (REACH-no) 01-2119456620-43	1 – 10	Asp. Tox. 1, H304
Diiron trioxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 1309-37-1 (EC-No.) 215-168-2 (REACH-no) 01-2119457614-35	< 5	Not classified
calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9 (REACH-no) 01-2119475325-36	< 2,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
chromium oxide substance with a Community workplace exposure limit	(CAS-No.) 1308-38-9 (EC-No.) 215-160-9 (REACH-no) 01-2119433951-39	< 2,5	Not classified
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (Note C)(Note 2)	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (EC Index-No.) 615-005-00-9 (REACH-no) 01-2119457014-47	0,1 - <1	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5 (EC-No.) 915-687-0 (REACH-no) 01-2119491304-40	< 0,1	Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

Specific concentration limits:

Name	Product identifier	Specific concentration limits
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (EC Index-No.) 615-005-00-9 (REACH-no) 01-2119457014-47	(0,1 C < 100) Resp. Sens. 1, H334 (5 C < 100) STOT SE 3, H335 (5 C < 100) Skin Irrit. 2, H315 (5 C < 100) Eye Irrit. 2, H319

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Move to fresh air. In all cases of doubt, or when symptoms persist, seek medical attention.
- First-aid measures after skin contact : After contact with skin, wash immediately and thoroughly with water and soap. Take off contaminated clothing and wash it before reuse. If symptoms persist call a doctor.
- First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide. Isocyanates. Hydrogen cyanide. Nitrogen oxides.

5.3. Advice for firefighters

Protection during firefighting : Wear self-contained breathing apparatus and protective suit (see section 8).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ensure adequate ventilation, especially in confined areas.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Keep in suitable, closed containers for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Do not breathe vapour or spray.
- Precautions for safe handling : Obtain special instructions before use. Wear protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

No additional information available

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

calcium oxide (1305-78-8)		
EU	Local name	Calcium oxide
EU	IOELV TWA (mg/m ³)	4 mg/m ³
EU	IOELV STEL (mg/m ³)	1 mg/m ³

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

calcium oxide (1305-78-8)		
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom	WEL TWA (mg/m ³)	2 mg/m ³
Titanium dioxide (13463-67-7)		
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Hydrocarbons, C11-C14, n-alkanes, iso-alkanes, cyclic, <2% aromatic		
EU	IOELV STEL (mg/m ³)	1200 mg/m ³
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)		
EU	IOELV TWA (mg/m ³)	0,052 mg/m ³
EU	IOELV TWA (ppm)	0,005 ppm
chromium oxide (1308-38-9)		
EU	IOELV TWA (mg/m ³)	2 mg/m ³
Diiron trioxide (1309-37-1)		
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Local exhaust or breathing protection.

Hand protection:

Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Polyvinylalcohol (PVA)				EN ISO 374

Eye protection:

Type	Use	Characteristics	Standard
Safety glasses		With side shields	EN 166

Skin and body protection:

Protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Gas filters	Type A - High-boiling (>65 °C) organic compounds, Type P1, Type P2, Type P3	If conc. in air > exposure limit	EN 140, EN 136



Consumer exposure controls:

Avoid contact with skin and eyes.

Other information:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: According to product specification.

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour	: Slight.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not determined
Freezing point	: No data available
Boiling point	: 137 °C
Flash point	: 70 °C ISO 3679
Auto-ignition temperature	: 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1,16 at 20 °C
Solubility	: Insoluble. Water: Insoluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0,6 – 8 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

No polymerization.

10.4. Conditions to avoid

None under normal use.

10.5. Incompatible materials

alcohols. Amines. Strong acids. alkali metals. Water. Alkaline earth metals.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg (OECD 425 method)
LD50 dermal rat	> 10000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 inhalation rat (mg/l)	> 6,82 mg/l
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 6,82 mg/l/4h

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C11-C14, n-alkanes, iso-alkanes, cyclic, <2% aromatic	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 5000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5000 mg/m ³ (OECD 403 method)

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 9400 mg/kg
LC50 inhalation rat (mg/l)	0,49 mg/l/4h

reaction mass of ethylbenzene and xylene	
LD50 oral rat	3523 – 4000 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 inhalation rat (mg/l)	6,35 mg/l/4h

chromium oxide (1308-38-9)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5,41 mg/l/4h (OECD 403 method)

Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not irritating to rabbits on ocular application (Based on available data, the classification criteria are not met)
Additional information	: (OECD 405 method)
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Not classified.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

chromium oxide (1308-38-9)	
LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight/day (OECD 408 method)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	: No information available.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

Titanium dioxide (13463-67-7)	
LC50 fish 1	> 1000 mg/l pimephales promelas
LC50 fish 2	> 10000 mg/l
EC50 Daphnia 1	> 100 mg/l (OECD 202 method)
EC50 other aquatic organisms 1	> 1000 mg/l
EC50 other aquatic organisms 2	61 mg/l
EC50 72h algae (2)	> 100 mg/l pseudokirchneriella subcapitata
NOEC chronic algae	5600 mg/l

Hydrocarbons, C11-C14, n-alkanes, iso-alkanes, cyclic, <2% aromatic	
EC50 Daphnia 1	> 1000 mg/l (OECD 202 method)

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
LC50 fish 1	1000 mg/l
EC50 Daphnia 1	1000 mg/l
NOEC (chronic)	10 mg/l Daphnia magna (Big water flea)
reaction mass of ethylbenzene and xylene	
NOEC chronic fish	1,3 mg/l
NOEC chronic crustacea	0,96 mg/l
NOEC chronic algae	0,44 mg/l
chromium oxide (1308-38-9)	
LC50 fish 1	> 10000 mg/l (OECD 210 method)
NOEC chronic fish	1000 mg/l (OECD 210 method)

12.2. Persistence and degradability

Titanium dioxide (13463-67-7)	
Persistence and degradability	Not readily biodegradable.
Hydrocarbons, C11-C14, n-alkanes, iso-alkanes, cyclic, <2% aromatic	
Biodegradation	69 % (OECD 301F method)
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
Biodegradation	(OECD 301F method)
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
Persistence and degradability	Not easily bio-degradable (according to OECD-criteria).
Biodegradation	28d 0 %
reaction mass of ethylbenzene and xylene	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
Partition coefficient n-octanol/water (Log Pow)	2,37 – 2,77 (OECD 107 method)
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
Bioconcentration factor (BCF REACH)	200
Partition coefficient n-octanol/water (Log Pow)	4,51
Bioaccumulative potential	highly bioaccumulative.
reaction mass of ethylbenzene and xylene	
Partition coefficient n-octanol/water (Log Kow)	3,16 at 20 °C
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

reaction mass of ethylbenzene and xylene	
Surface tension	28,7 mN/m at 25 °C
Ecology - soil	Floats on water.

12.5. Results of PBT and vPvB assessment

Detaflex 4000	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

Additional information : Do not allow into drains or water courses

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : This material and its container must be disposed of as hazardous waste.
 Sewage disposal recommendations : Disposal must be done according to official regulations.

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Product/Packaging disposal recommendations : Dispose of at a licensed waste collection centre. Hand over to officially registered waste disposal company.
European List of Waste (LoW) code : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

- Overland transport
Not applicable
- Transport by sea
Not applicable
- Air transport
Not applicable
- Inland waterway transport
Not applicable
- Rail transport
Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	reaction mass of ethylbenzene and xylene
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Hydrocarbons, C11-C14, n-alkanes, iso-alkanes, cyclic, <2% aromatic ; Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; reaction mass of ethylbenzene and xylene
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	reaction mass of ethylbenzene and xylene

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

56. Methylenediphenyl diisocyanate (MDI)	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate
56(a) Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Dam./Irrit. Not classified	Serious eye damage/eye irritation Not classified
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. Not classified	Skin sensitisation Not classified
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH204	Contains isocyanates. May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Eye Dam./Irrit. Not classified		Expert judgment
Resp. Sens. 1	H334	Calculation method
Skin Sens. Not classified		Expert judgment

Detaflex 4000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Reach Annex II DL-Chem

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.