

Version: 1

Revision Date: 22.09.2020

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

EUCOCOAT EP ECO S - B

1.2 Relevant identified uses of the substance or mixture and uses advised against:

For professional use only Concentration in use: /

1.3. Details of the supplier of the safety data sheet

EUCOCHEM BV ESPERANTOLAAN 13/7 B-3300 TIENEN BELGIUM

Tel.: +32.16.81.11.52

E-Mail: office@eucochem.com

1.4. Emergency telephone number

+32 70 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008: H318 Eye Dam. 1

2.2 Label elements:

Pictograms:



Signal word: Danger



Version: 1

Revision Date: 22.09.2020

Hazard statements:

H318 Eye Dam. 1: Causes serious eye damage.

Precautionary statements:

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

Contains:

Polymer, reaction product of glycidylether with TEPA

2.3 Other hazards:

None

SECTION 3: Composition / information on ingredients

Barium sulphate	≤ 40 %	CAS number: EINECS: REACH Registration number: CLP Classification:	7727-43-7 231-784-4 Annex V
Polymer, reaction product of glycidylether with TEPA	≤9%	CAS number: EINECS: REACH Registration number: CLP Classification:	155240-09-8 H318 Eye Dam. 1

For the full text of the H phrases mentioned in this section, see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur. Skin contact: Remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.

Eye contact: Thoroughly rinse with water (contact lenses to be removed if this is easily done) Then take to physician.

Ingestion: Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.



Version:

Revision Date: 22.09.2020

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: Caustic, redness, pain, serious burns Eye contact: Caustic, redness, blurred vision, pain

Ingestion: Caustic, lack of breath, vomiting, blisters on lips and tongue,

burning pain in mouth and throat, gullet and stomach

Inhalation: Headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

None

SECTION 5: Firefighting measures

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind.

Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.



Version:

Revision Date: 22.09.2020

6.4 Reference to other sections:

For further information, check sections 8 & 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

For professional use only

SECTION 8: Exposure controls / personal protection

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known 2-butoxyethanol 98 mg/m³, Barium sulphate 5 mg/m³

8.2 Exposure controls:

Inhalation protection:	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	



Version: 1

Revision Date: 22.09.2020

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Melting point/melting range: 0 °C

Boiling point/Boiling range: 100 °C — 173 °C

pH: /

pH 1% diluted in water: /

Vapour pressure/20°C,: 2 332 Pa Vapour density: Not applicable Relative density, 20°C: / Appearance/20°C: Liquid

Flash point: /

Flammability (solid, gas): Not applicable

Auto-ignition temperature: /

Upper flammability or explosive limit, (Vol %): / Lower flammability or explosive limit, (Vol %): /

Explosive properties: Not applicable Oxidising properties: Not applicable Decomposition temperature: / Solubility in water: Not soluble

Partition coefficient: noctanol/water: Not applicable

Odour: characteristic

Odour threshold: Not applicable Dynamic viscosity, 20°C: / Kinematic viscosity, 40°C: /

Evaporation rate (n-BuAc = 1): 0.300

9.2 Other information:

Volatile organic component (VOC): 0.24 % Volatile organic component (VOC): /
Sustained combustion test: /

SECTION 10: Stability and reactivity

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.



Version:

Revision Date: 22.09.2020

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

None

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

H318 Eye Dam. 1: Causes serious eye damage.

Calculated acute toxicity, ATE oral: / Calculated acute toxicity, ATE dermal: /

Barium sulphate	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Polymer, reaction product of glycidylether with TEPA	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l

SECTION 12: Ecological information

12.1 Toxicity:

No additional data available

12.2 Persistence and degradability:

No additional data available



Version:

Revision Date: 22.09.2020

12.3 Bioaccumulative potential:

No additional data available

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 1 Solubility in water: Not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

÷

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

SECTION 14: Transport information

14.1 UN number:

Not applicable

14.2 UN proper shipping name:

ADR, IMDG, ICAO/IATA not applicable

14.3 Transport hazard class(es):

Class(es): Not applicable

Identification number of the hazard: Not applicable

14.4 Packing group:

Not applicable



Version: 1

Revision Date: 22.09.2020

14.5 Environmental hazards:

Not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: Not applicable Additional guidance: Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1

Volatile organic component (VOC): 0.245 %

Volatile organic component (VOC): /

Composition by regulation (EC) 648/2004: None

15.2 Chemical Safety Assessment:

No data available

SECTION 16: Other information

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE: Acute Toxicity Estimate BCF: Bioconcentration factor CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

LD50: median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative

TLV: Threshold Limit Value

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

WGK 1: Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

Safety Data Sheet According to Regulation (EC) No. 1907/2006



Trade Name: EUCOCOAT EP ECO S - B

Version: 1

Revision Date: 22.09.2020

Legend to the H Phrases used in the safety data sheet:

H318 Eye Dam. 1: Causes serious eye damage. CLP Calculation method: Calculation method

Reason of revision, changes of following items: Sections: 9.1, 9.2

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application , the user must carry out a material suitability and safety study himself.