

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

## SECTION 1: Identification of the substance / mixture and of the company / undertaking

### 1.1. Product identifier

EUCOGROUT EP L - B

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

For professional use only

Concentration in use: /

### 1.3. Details of the supplier of the safety data sheet

EUCCHEM BV  
ESPERANTOLAAN 13/7  
B-3300 TIENEN  
BELGIUM  
Tel.: +32.16.81.11.52  
E-Mail: office@euccchem.com

### 1.4. Emergency telephone number

+32 70 245 245

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H314 Skin Corr. 1A H317 Skin Sens. 1 H335 STOT SE 3 H361f Repr. 2

H400 Aquatic Acute 1 H410 Aquatic Chronic 1

### 2.2 Label elements:

Pictograms:



Signal word: Danger

Hazard statements:

H314 Skin Corr. 1A: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction.

H335 STOT SE 3: May cause respiratory irritation.

H361f Repr. 2: Suspected of damaging fertility.

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

H400 Aquatic Acute 1 H410 Aquatic

Chronic 1:

Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains:

tert.-butylphenol m-phenylenebis(methylamine) Styrenated phenol Benzyl alcohol

### 2.3 Other hazards:

none

## SECTION 3: Composition / information on ingredients

tert.-butylphenol	> 30%	CAS number: 98-54-4 EINECS: 202-679-0 REACH Registration number: 01-2119489419-21 CLP Classification: H315 Skin Irrit. 2 H318 Eye Dam. 1 H335 STOT SE 3 H361f Repr. 2 H400 Aquatic Acute 1 H410 Aquatic Chronic 1
m-phenylenebis(methylamine)	15% - 30%	CAS number: 1477-55-0 EINECS: 216-032-5 REACH Registration number: 01-2119480150-50 CLP Classification: H302 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H332 Acute tox. 4 H412 Aquatic Chronic 3
Benzyl alcohol	5% - 15%	CAS number: 100-51-6 EINECS: 202-859-9 REACH Registration number: 01-2119492630-38 CLP Classification: H302 Acute tox. 4 H319 Eye Irrit. 2 H332 Acute tox. 4

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

Styrenated phenol	5% - 15%	CAS number: 61788-44-1 EINECS: 262-975-0 REACH Registration number: 01-2119980970-27 CLP Classification: H315 Skin Irrit. 2 H317 Skin Sens. 1 H411 Aquatic Chronic 2
Trimethylhexane-1,6-diamine	5% - 15%	CAS number: 25620-58-0 EINECS: 247-134-8 REACH Registration number: CLP Classification: H302 Acute tox. 4 H314 Skin Corr. 1A H317 Skin Sens. 1 H412 Aquatic Chronic 3

For the full text of the H & R phrases mentioned in this section, see section 16

## SECTION 4: First aid measures

### 4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.

Eye contact: first prolonged rinsing with water (contact lenses to be removed if this is easily done) then take to physician.

Ingestion: rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: let sit upright, fresh air, rest and take to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: caustic, redness, pain, serious burns

Eye contact: caustic, redness, bad looking, pain

Ingestion: caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, gullet and stomach

Inhalation: headache, dizziness, nausea, drowsiness, unconsciousness

### 4.3 Indication of any immediate medical attention and special treatment needed:

None

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media:

CO<sub>2</sub>, foam, powder, sprayed water

### 5.2 Special hazards arising from the substance or mixture:

none

### 5.3 Advice for firefighters:

Extinguishing agents to be avoided: none

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

### 6.2 Environmental precautions:

do not allow to flow into sewers or open water.

### 6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible remove by using absorbent material.

### 6.4 Reference to other sections:

for further information check sections 8 & 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling:

handle with care to avoid spillage.

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

## 7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

## 7.3 Specific end use(s):





For professional use only

# SECTION 8: Exposure controls / personal protection

## 8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known /

## 8.2 Exposure controls:

<b>Inhalation protection:</b>	use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
<b>Skin protection:</b>	handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
<b>Eye protection:</b>	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
<b>Other protection:</b>	impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties:

Melting point/melting range: /  
Boiling point/Boiling range: 205 °C — 272 °C  
pH: 12.0  
pH 1% diluted in water: /  
Vapour pressure/20°C,: /  
Vapour density: not applicable  
Relative density, 20°C: 1.0300 kg/l  
Appearance/20°C: liquid  
Flash point: /

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

---

Flammability (solid, gas): not applicable  
Auto-ignition temperature: /  
Upper flammability or explosive limit, (Vol %): /  
Lower flammability or explosive limit, (Vol %): /  
Explosive properties: not applicable  
Oxidising properties: not applicable  
Decomposition temperature: /  
Solubility in water: not soluble  
Partition coefficient: octanol/water: not applicable  
Odour: characteristic  
Odour threshold: not applicable  
Dynamic viscosity, 20°C: 2 500 mPa.s  
Kinematic viscosity, 40°C: 2 427 mm<sup>2</sup>/s  
Evaporation rate (n-BuAc = 1): 0.010

**9.2 Other information:**

Volatile organic component (VOC): 8.50 %  
Volatile organic component (VOC): 87.550 g/l

## SECTION 10: Stability and reactivity

**10.1 Reactivity:**

stable under normal conditions.

**10.2 Chemical stability:**

extremely high or low temperatures.

**10.3 Possibility of hazardous reactions:**

None

**10.4 Conditions to avoid:**

protect from sunlight and do not expose to temperatures exceeding + 50°C.

**10.5 Incompatible materials:**

acids, alkalines, oxidants, reductants

**10.6 Hazardous decomposition products:**

doesn't decompose with normal use

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects:

H314 Skin Corr. 1A: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction.

H335 STOT SE 3: May cause respiratory irritation.

H361f Repr. 2: Suspected of damaging fertility.

Calculated acute toxicity, ATE oral: 1 491.109 mg/kg

Calculated acute toxicity, ATE dermal: /

tert.-butylphenol	LD50 oral, rat: 2,951 mg/kg LD50 dermal, rabbit: 2,288 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
m-phenylenebis(methylamine)	LD50 oral, rat: 980 mg/kg LD50 dermal, rabbit: 3,100 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
Benzyl alcohol	LD50 oral, rat: 1,230 mg/kg LD50 dermal, rabbit: 1,100 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
Styrenated phenol	LD50 oral, rat: ≥ 5,000 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
Trimethylhexane-1,6-diamine	LD50 oral, rat: 500 mg/kg LD50 dermal, rabbit: ≥ 5,000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l

## SECTION 12: Ecological information

### 12.1 Toxicity:

tert.-butylphenol	LC50 (Fish): > 1 mg/L (96h) EC50 (Daphnia): ca. 4.8 mg/L (48h) NOEC (Daphnia): ca. 3.2 mg/L (48h) EC50 (Algae): ca. 14 mg/L (72h) EC50 (soil microorganisms): > 10 mg/L (3h)
-------------------	--



Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

m-phenylenebis(methylamine)	LC50 (Fish): 87.6 mg/L (96h) EC50 (Daphnia): 87.6 mg/L (96h) EC50 (Algae): 20.3 mg/L (72h) EC50 (soil microorganisms): > 1000 mg/L (30min)
Benzyl alcohol	LC50 (Fish): 460 mg/L (72h) EC50 (Daphnia): 230 mg/L (48h) NOEC (Daphnia): 310 mg/L (72h) EC50 (Algae): 770 mg/L (72h)
Styrenated phenol	LC50 (Fish): 5.6 mg/L (4d) NOEC (Fish): 1.9 mg/L (14d) EC50 (Daphnia): 1.44 - 4.6 mg/L (45h) EC50 (Algae): 1.5 mg/L (21d) NOEC (Algae): 115 - 200 µg/L (21d)

## 12.2 Persistence and degradability:

No additional data available

## 12.3 Bioaccumulative potential:

No additional data available

## 12.4 Mobility in soil:

Water hazard class, WGK: 1  
Solubility in water: not soluble

## 12.5 Results of PBT and vPvB assessment:

No additional data available

## 12.6 Other adverse effects:

No additional data available

# SECTION 13: Disposal considerations

## 13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.



Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

---

## SECTION 14: Transport information

### 14.1 UN number:

2735

### 14.2 UN proper shipping name:

UN 2735 Amines, liquid, corrosive, n.o.s. (mixture with Trimethylhexane-1,6-diamine; m-phenylenebis(methylamine)) , 8, II, (E)

### 14.3 Transport hazard class(es):

Class(es): 8

Identification number of the hazard: 80

### 14.4 Packing group:

II

### 14.5 Environmental hazards:

environmentally hazardous

### 14.6 Special precautions for user:

Hazard characteristics: Risk of burns. Risk to the aquatic environment and the sewerage system.

Additional guidance:



Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK: 1  
Volatile organic component (VOC): 8.500 %  
Volatile organic component (VOC): 87.550 g/l  
Composition by regulation (EC) 648/2004: Aromatic hydrocarbons > 30%

### 15.2 Chemical Safety Assessment:

No data available

## SECTION 16: Other information

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF: Bioconcentration factor  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging of chemicals  
EINECS: European INventory of Existing Commercial chemical Substances  
Nr.: number  
PTB: persistent, toxic, bioaccumulative  
TLV: Threshold Limit Value  
vPvB: very persistent and very bioaccumulative substances  
WGK: Water hazard class  
WGK 1: slightly hazardous for water  
WGK 2: hazardous for water  
WGK 3: extremely hazardous for water

Legend to the R & H Phrases used in the safety data sheet:

H302 Acute tox. 4: Harmful if swallowed.  
H314 Skin Corr. 1A: Causes severe skin burns and eye damage.  
H314 Skin Corr. 1B: Causes severe skin burns and eye damage.  
H315 Skin Irrit. 2: Causes skin irritation.  
H317 Skin Sens. 1: May cause an allergic skin reaction.  
H318 Eye Dam. 1: Causes serious eye damage.  
H319 Eye Irrit. 2: Causes serious eye irritation.  
H332 Acute tox. 4: Harmful if inhaled. H335 STOT SE 3: May cause respiratory irritation.  
H361f Repr. 2: Suspected of damaging fertility.

Trade Name: EUCOGROUT EP L - B  
Version: 1  
Revision Date: 24.09.2020

---

H400 Aquatic Acute 1: Very toxic to aquatic life.

H400 Aquatic Acute 1

H410 Aquatic Chronic 1: Very toxic to aquatic life with long lasting effects.

H410 Aquatic Chronic 1: Very toxic to aquatic life with long lasting effects.

H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Reason of revision, changes of following items: Section: 11

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.