EUCOMARK ACRYLIC



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAI

1.1 Product identifier: EUCOMARK ACRYLIC

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Road sign paint: zebra crossings, yellow boxes, etc.... For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

EUCOCHEM BV Esperantolaan 13/7 B - 3300 Tienen BELGIUM Tél : +32 16 81 11 52 E-mail : office@eucochem.com

1.4 Emergency telephone number: +32 70 245 245

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 2: Flammable liquids, Category 2, H225 Skin Irrit. 2: Skin irritation, Category 2, H315

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P264: Wash thoroughly after handling P280: Wear protective gloves/protective clothing/eye protection/face protection P302:P352: IF ON SKIN: Wash with plenty of water P305:P351:P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P370:P378: In case of fire: Use ABC powder extinguisher to extinguish P403:P235: Store in a well-ventilated place. Keep cool P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance: Non-applicable 3.2 Mixture: Chemical description: Acrylic resin Components:





SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS:		Butanone ⁽¹⁾		ATP CLP00	
EC: 201-159-0 Index: 606-002-00-3 REACH 01-2119457290-43-XXXX :		Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	(1) (1)	10 - fi25 %
CAS:	1330-20-7 215-535-7	Xylene ⁽¹⁾		ATP CLP00	
Index: 601-0	213-535-7 601-022-00-9 1 01-2119488216-32-XXXX	Regulation 1272/2008	Acute Tox. 4: H312 H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	(1) (1)	10 - fi25 %
CAS:		alkanes, C14-17, chloro ⁽¹	0	ATP ATP01	
EC: Index: REACH :	287-477-0 602-095-00-X H 01-2119519269-33-XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362; EUH066 - Warning	È	fil %
CAS:		phosphorus pentoxide ⁽²⁾		ATP CLP00	
Index:	215-236-1 015-010-00-0 4 01-2119489912-25-XXXX	Regulation 1272/2008	Skin Corr. 1A: H314 - Danger		fi1 %

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist. **By skin contact:**

Dy Skill Collider.

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:





SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

Methods and material for containment and cleaning up:

It is recommended:

6.3

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 🛛 C
Maximum Temp.:	30 □C
Maximum time:	12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5





SECTION 7: HANDLING AND STORAGE (continued)

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

TION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Identification	Occupational exposure limits		
Butanone	IOELV (8h)	200 ppm	600 mg/m ³
CAS: 78-93-3 EC: 201-159-0	IOELV (STEL)	300 ppm	900 mg/m ³
Xylene	IOELV (8h)	50 ppm	221 mg/m³
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³
phosphorus pentoxide	IOELV (8h)		1 mg/m ³
CAS: 1314-56-3 EC: 215-236-1	IOELV (STEL)		

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m³	442 mg/m ³	221 mg/m³	221 mg/m³
alkanes, Cl4-17, chloro	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 85535-85-9	Dermal	Non-applicable	Non-applicable	47,9 mg/kg	Non-applicable
EC: 287-477-0	Inhalation	Non-applicable	Non-applicable	6,7 mg/m ³	Non-applicable
phosphorus pentoxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1314-56-3	Dermal	Non-applicable	Non-applicable	68,7 mg/kg	Non-applicable
EC: 215-236-1	Inhalation	Non-applicable	Non-applicable	1 mg/m³	Non-applicable

DNEL (General population):

		Short exposure		Lo	Long exposure	
Identification		Systemic	Local	Systemic	Local	
Butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable	
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable	
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m³	Non-applicable	
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	260 mg/m³	260 mg/m³	65,3 mg/m³	65,3 mg/m³	
alkanes, Cl4-17, chloro	Oral	Non-applicable	Non-applicable	0,58 mg/kg	Non-applicable	
CAS: 85535-85-9	Dermal	Non-applicable	Non-applicable	28,75 mg/kg	Non-applicable	
EC: 287-477-0	Inhalation	Non-applicable	Non-applicable	2 mg/m ³	Non-applicable	
phosphorus pentoxide	Oral	Non-applicable	Non-applicable	68,7 mg/kg	Non-applicable	
CAS: 1314-56-3	Dermal	Non-applicable	Non-applicable	68,7 mg/kg	Non-applicable	
EC: 215-236-1	Inhalation	Non-applicable	Non-applicable	1 mg/m³	Non-applicable	
PNEC:						
Identification						
Butanone	STP	709 mg/L	Fresh water		55,8 mg/L	
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water		55,8 mg/L	
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh w	vater)	284,74 mg/kg	
	Oral	1 g/kg	Sediment (Marine	water)	284,7 mg/kg	





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
alkanes, Cl4-17, chloro	STP	80 mg/L	Fresh water	0,001 mg/L
CAS: 85535-85-9	Soil	11,9 mg/kg	Marine water	0,0002 mg/L
EC: 287-477-0	Intermittent	Non-applicable	Sediment (Fresh water)	13 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	2,6 mg/kg
phosphorus pentoxide	STP	10 mg/L	Fresh water	0,0665 mg/L
CAS: 1314-56-3	Soil	0,0107 mg/kg	Marine water	0,00665 mg/L
EC: 215-236-1	Intermittent	0,665 mg/L	Sediment (Fresh water)	0,249 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0249 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding fifiCE markingflfl in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2003 Al:2009 and EN ISO 374-1:2016

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks			
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.			
Body protection							
Pictogram	PPE	Labelling	CEN Standard	Remarks			
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN 168:2015 EN 150 14116:2015 EN 1149-5:2018	Limited protection against flames.			
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	CAT III	EN ISO 13287:2012 EN ISO 20345:2011	Replace boots at any sign of deterioration.			

F.- Additional emergency measures





Emergency measure	Standards	Emergency measure	Standards	
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011			
Environmental exposure contro				
With regard to Directive 2010/2	75/EU, this product has the following ch	naracteristics:		
Volatile organic compounds:				
With regard to Directive 2010/2	75/EU, this product has the following ch	aracteristics:		
V.O.C. (Supply):	28,18 % weight			
V.O.C. density at 20 C:	422,7 kg/m³ (422,7 g/L)	422,7 kg/m³ (422,7 g/L)		
	<i>E</i> 01	5,91		
Average carbon number:	5,91			
Average carbon number: Average molecular weight:	3,91 88,41 g/mol			
Average molecular weight:	- , -	se has the following charact	eristics:	
Average molecular weight:	88,41 g/mol	se has the following charact	eristics:	
Average molecular weight: With regard to Directive 2004/	88,41 g/mol 42/EC, this product which is ready to u 422,7 kg/m³ (422,7 g/L)	se has the following charact	eristics:	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

1	Information on basic physical and chemical properties:	
	For complete information see the product datasheet.	
	Appearance:	
	Physical state at 20 C:	Liquid
	Appearance:	Fluid
	Colour:	White
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	100 IC
	Vapour pressure at 20 C:	6103 Pa
	Vapour pressure at 50 ^[] C:	23140,88 Pa (23,14 kPa)
	Evaporation rate at 20 C:	Non-applicable *
	Product description:	
	Density at 20 C:	1500 kg/m³
	Relative density at 20 C:	1,5
	Dynamic viscosity at 20 C:	Non-applicable *
	Kinematic viscosity at 20 C:	Non-applicable *
	Kinematic viscosity at 40 C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 C:	Non-applicable *
	Partition coefficient n-octanol/water 20 []C:	Non-applicable *
	Solubility in water at 20 C:	Non-applicable *
	Solubility properties:	Insoluble in water, soluble in organic solvents





SEC	TION 9: PHYSICAL AND CHEMICAL PROP	ERTIES (continued)
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	13 IC
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	465 IC
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Explosive:	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
9.2	Other information:	
	Surface tension at 20 \Box C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing informat	ion property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable
10.5	Incompatible materials:				
	Acids	Water	Oxidising materials	Combustible materials	Others

Actus Water Obtaining materialis Combustible materialis Others Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):





SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: Xylene (3); Titanium dioxide (aerodynamic diameter □ 10 µm) (2B); Silicon dioxide (RCS fi 1%) (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation	23,5 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:





SECTION 12: ECOLOGICAL INFORMATION (continue)

Identification		Acute toxicity	Species	Genus
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 215-535-7		10 mg/L (72 h)	Skeletonema costatum	Algae
alkanes, Cl4-17, chloro	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 85535-85-9	EC50	0.1 - 1 mg/L		Crustacean
EC: 287-477-0	EC50	0.1 - 1 mg/L		Algae

12.2 Persistence and degradability:

Identification	Deg	radability	Biodegradability	
Butanone	BOD5	2.03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2.31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0.88	% Biodegradable	89 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
Butanone	BCF	3	
CAS: 78-93-3	Pow Log	0.29	
EC: 201-159-0	Potential	Low	
Xylene	BCF	9	
CAS: 1330-20-7	Pow Log	2.77	
EC: 215-535-7	Potential	Low	

12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		Volatility	
Butanone	Koc	30	Henry	5,77 Pa·m³/mol	
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes	
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 C)	Moist soil	Yes	
Xylene	Koc	202	Henry	524,86 Pa·m³/mol	
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes	
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP4 Irritant - skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.





SECTION 13: DISPOSAL CONSIDERATIONS (continued

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

C	14.1	UN number:	UN1263
	14.2	UN proper shipping name:	PAINT
JAL.	14.3	Transport hazard class(es):	3
		Labels:	3
	14.4	Packing group:	II
3	14.5	Environmental hazards:	No
V	14.6	Special precautions for user	
		Special regulations:	163, 367, 640D, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Transport in bulk according to	Non-applicable
		Annex II of Marpol and the IBC	
		Code:	
Transport of dang	gerous g	oods by sea:	
With regard to IN	4DG 39)-18:	
	14.1	UN number:	UN1263
	14.2	UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
		Labels:	3
$\langle - \rangle$	14.4	Packing group:	II
	14.5	Environmental hazards:	No
3	14.6	Special precautions for user	
•		Special regulations:	367, 163
		EmS Codes:	F-E, S-E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		Segregation group:	Non-applicable
	14.7	Transport in bulk according to	Non-applicable
		Annex II of Marpol and the IBC	
Transport of dom	tomorro d	Code:	
Transport of dang	, U		
With regard to IA			113,110,00
	14.1	UN number:	UN1263
	14.2	UN proper shipping name:	PAINT
$\langle - \rangle$	14.3	Transport hazard class(es): Labels:	3 3
2	14.4	Packing group:	II
	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
	A A.U	Physico-Chemical properties:	see section 9
	14.7	Transport in bulk according to	Non-applicable
		Annex II of Marpol and the IBC	T.L.
		Code:	

** Changes with regards to the previous version





15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtravs.

tricks and jokes,

games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product. Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

TRANSPORT INFORMATION (SECTION 14):

- · UN number
- · Packing group

Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour

H315: Causes skin irritation

H319: Causes serious eye irritation

H412: Harmful to aquatic life with long lasting effects

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3





CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312 H332 - Harmful in contact with skin or if inhaled Aquatic Acute 1: H400 - Very toxic to aquatic life Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects Éye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour Lact.: H362 - May cause harm to breast-fed children Skin Corr. 1A: H314 - Causes severe skin burns and eye damage Skin Irrit. 2: H315 - Causes skin irritation STOT SE 3: H336 - May cause drowsiness or dizziness

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.