

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

EUCOREP EP FLOOR - A

1.2 Relevant identified uses of the substance or mixture and uses advised against:

For professional use only

Concentration in use: /

1.3. Details of the supplier of the safety data sheet

EUCCHEM BV

ESPERANTOLAAN 13/7

B-3300 TIENEN

BELGIUM

Tel.: +32.16.81.11.52

E-Mail: office@euccchem.com

1.4. Emergency telephone number

+32 70 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H315 Skin Irrit. 2 H317 Skin Sens. 1 H319 Eye Irrit. 2 H411 Aquatic Chronic 2

2.2 Label elements:

Pictograms:



Signal word: Warning

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

Hazard statements:

H315 Skin Irrit. 2: Causes skin irritation.
H317 Skin Sens. 1: May cause an allergic skin reaction.
H319 Eye Irrit. 2: Causes serious eye irritation.
H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Precautionary statements:

P280: Wear protective gloves, protective clothing, eye protection, face protection.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P337+P313: If eye irritation persists: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.

Contains:

Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight ≤ 700)
Reaction product of
Bisphenol-F-epichlorhydrin epoxy resin Alkyl glycidyl ether

2.3 Other hazards:

None

SECTION 3: Composition / information on ingredients

Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight ≤ 700)	$\leq 60 \%$	CAS number: 1675-54-3 EINECS: 216-823-5 REACH Registration number: 01-2119456619-26 CLP Classification: H315 Skin Irrit. 2 H317 Skin Sens. 1 H319 Eye Irrit. 2 H411 Aquatic Chronic 2
Reaction product of Bisphenol-F-epichlorhydrin epoxy resin	$\leq 30 \%$	CAS number: 9003-36-5 EINECS: 701-263-0 REACH Registration number: 01-2119454392-40 CLP Classification: H315 Skin Irrit. 2 H317 Skin Sens. 1 H411 Aquatic Chronic 2
Alkyl glycidyl ether	$\leq 10 \%$	CAS number: 68609-97-2 EINECS: 271-846-8 REACH Registration number: 01-2119485289-22 CLP Classification: H315 Skin Irrit. 2 H317 Skin Sens. 1

For the full text of the H phrases mentioned in this section, see section 16.

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

SECTION 4: First aid measures

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: Remove contaminated clothing, rinse skin with plenty of water, if necessary seek medical attention.

Eye contact: Thoroughly rinse with water (contact lenses to be removed if this is easily done) then take to physician.

Ingestion: Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: Redness, pain

Eye contact: Redness, pain, blurred vision

Ingestion: Diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: Sore throat, cough, shortness of breath, headache

4.3 Indication of any immediate medical attention and special treatment needed:

None

SECTION 5: Firefighting measures

5.1 Extinguishing media:

CO₂, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

For professional use only





SECTION 8: Exposure controls / personal protection

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known /

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

8.2 Exposure controls:

Inhalation protection:	If necessary, use an air-purifying face mask in case of respiratory hazards.	
Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Melting point/melting range: /
Boiling point/Boiling range: 394 °C — 394 °C
pH: /
pH 1% diluted in water: /
Vapour pressure/20°C,: /
Vapour density: Not applicable
Relative density, 20°C: /
Appearance/20°C: Liquid
Flash point: /
Flammability (solid, gas): Not applicable
Auto-ignition temperature: 330 °C
Upper flammability or explosive limit, (Vol %): /
Lower flammability or explosive limit, (Vol %): /
Explosive properties: Not applicable
Oxidising properties: Not applicable
Decomposition temperature: /
Solubility in water: Not soluble
Partition coefficient: noctanol/water: Not applicable
Odour: characteristic
Odour threshold: Not applicable
Dynamic viscosity, 20°C: 1 mPa.s
Kinematic viscosity, 40°C: /
Evaporation rate (n-BuAc = 1): /

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

9.2 Other information:

Volatile organic component (VOC): /
Volatile organic component (VOC): /
Sustained combustion test : /

SECTION 10: Stability and reactivity

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

None

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

H315 Skin Irrit. 2: Causes skin irritation.
H317 Skin Sens. 1: May cause an allergic skin reaction.
H319 Eye Irrit. 2: Causes serious eye irritation.
Calculated acute toxicity, ATE oral: /
Calculated acute toxicity, ATE dermal: /

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight \leq 700)	LD50 oral, rat: \geq 5 000 mg/kg LD50 dermal, rabbit: \geq 5 000 mg/kg LC50, Inhalation, rat, 4h: \geq 50 mg/l
Reaction product of Bisphenol-F-epichlorhydrin epoxy resin	LD50 oral, rat: \geq 5 000 mg/kg LD50 dermal, rabbit: \geq 5 000 mg/kg LC50, Inhalation, rat, 4h: \geq 50 mg/l
Alkyl glycidyl ether	LD50 oral, rat: \geq 5 000 mg/kg LD50 dermal, rabbit: \geq 5 000 mg/kg LC50, Inhalation, rat, 4h: \geq 50 mg/l

SECTION 12: Ecological information

12.1 Toxicity:

Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight \leq 700)	LC50 (Fish): 3.6 mg/L (96h) EC50 (Daphnia): 1.1 mg/L (48h) EC50 (Algae): 9.1 mg/L (48h) NOEC (Algae): 2.4 mg/L (72h)
Reaction product of Bisphenol-F-epichlorhydrin epoxy resin	LC50 (Fish): $>$ 1000 mg/L (96h) EC50 (Algae): $>$ 1.8 mg/L (72h)
Alkyl glycidyl ether	NOEC (Fish): 100 mg/L (96h) NOEC (Daphnia): 500 mg/L (72h)

12.2 Persistence and degradability:

No additional data available

12.3 Bioaccumulative potential:

No additional data available

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 3
Solubility in water: Not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

SECTION 14: Transport information

14.1 UN number:

3082

14.2 UN proper shipping name:

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (mixture with Reaction product of Bisphenol-A-epichlorhydrin epoxy resin (average molecular weight ≤ 700); Reaction product of Bisphenol-F-epichlorhydrin epoxy resin), 9, III, (E)

14.3 Transport hazard class(es):

Class(es): 9

Identification number of the hazard: 90

14.4 Packing group:

III


14.5 Environmental hazards:

Environmentally hazardous

14.6 Special precautions for user:

Hazard characteristics: Risk to the aquatic environment and the sewerage system.

Additional guidance:



Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 3
Volatile organic component (VOC): /
Volatile organic component (VOC): /
Composition by regulation (EC) 648/2004: None

15.2 Chemical Safety Assessment:

No data available

SECTION 16: Other information

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE: Acute Toxicity Estimate

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

LD50: median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative

TLV: Threshold Limit Value

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

WGK 1: Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

H315 Skin Irrit. 2: Causes skin irritation.

H317 Skin Sens. 1: May cause an allergic skin reaction.

H319 Eye Irrit. 2: Causes serious eye irritation.

H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

CLP Calculation method: Calculation method

Reason of revision, changes of following items: Section: 3

Trade Name: EUCOREP EP FLOOR - A
Version: 1
Revision Date: 13.10.2020

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.