

Version:

Revision Date: 23.09.2020

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

EUCOREP EP - B

1.2 Relevant identified uses of the substance or mixture and uses advised against:

For professional use only Concentration in use: /

1.2. Details of the supplier of the safety data sheet

EUCOCHEM BV ESPERANTOLAAN 13/7 B-3300 TIENEN BELGIUM

Tel.: +32.16.81.11.52

E-Mail: office@eucochem.com

1.3. Emergency telephone number

+32 70 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008: H302 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H341 Muta. 2 H412 Aquatic Chronic 3

2.2 Label elements:

Pictograms:



Signal word: Danger



Version:

Revision Date: 23.09.2020

Hazard statements:

H302 Acute tox. 4: Harmful if swallowed.

H314 Skin Corr. 1B: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction.

H341 Muta. 2: Suspected of causing genetic defects.

H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260: Do not breathe dust/vapours/spray.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains:

2,4,6-Tris(dimethyl amino methyl)phenol m-phenylenebis(methylamine) Benzyl alcohol Isophoronediamine

2.3 Other hazards:

None

SECTION 3: Composition / information on ingredients

Isophoronediamine	≤ 30 %	CAS number: EINECS: REACH Registration number:	2855-13-2 220-666-8 01-2119514687-32
		CLP Classification:	H302+H312 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H412 Aquatic Chronic 3
Benzyl alcohol	≤ 30 %	CAS number: EINECS: REACH Registration number:	100-51-6 202-859-9 01-2119492630-38
		CLP Classification:	H302 Acute tox. 4 H319 Eye Irrit. 2 H332 Acute tox. 4
m-phenylenebis(methylamine)	≤ 10 %	CAS number:	1477-55-0
		EINECS:	216-032-5
		REACH Registration number:	01-2119480150-50
		CLP Classification:	H302 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H332 Acute tox. 4 H412 Aquatic Chronic 3



Version: 1

Revision Date: 23.09.2020

2,4,6-Tris(dimethyl amino methyl)phenol	≤ 10 %	CAS number: EINECS: REACH Registration number: CLP Classification:	90-72-2 202-013-9 01-2119560597-27 H302 Acute tox. 4 H314 Skin Corr. 1C
Phenol	≤2%	CAS number: EINECS: REACH Registration number: CLP Classification:	108-95-2 203-632-7 01-2119471329-32 H301 Acute tox. 3 H311 Acute tox. 3 H314 Skin Corr. 1B H331 Acute tox. 3 H341 Muta. 2 H373 STOT RE 2

For the full text of the H phrases mentioned in this section, see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur. Skin contact: Remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.

Eye contact: Thoroughly rinse with water (contact lenses to be removed if this is easily done) Then take to physician.

Ingestion: Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: Caustic, redness, pain, serious burns Eye contact: Caustic, redness, blurred vision, pain

Ingestion: Caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth

and throat, gullet and stomach

Inhalation: Headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

None



Version: 1

Revision Date: 23.09.2020

SECTION 5: Firefighting measures

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Handle with care to avoid spillage.



Version: 1

Revision Date: 23.09.2020

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

For professional use only

SECTION 8: Exposure controls / personal protection

Inhalation protection:	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	Handling with Viton-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	

Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.			1	
-------------------	--	--	--	---	--

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Melting point/melting range: /

Boiling point/Boiling range: 205 °C — 272 °C

pH: /

pH 1% diluted in water: / Vapour pressure/20°C,: / Vapour density: Not applicable Relative density, 20°C: 1.0700 kg/l

Appearance/20°C: Liquid

Flash point: /

Flammability (solid, gas): Not applicable Auto-ignition temperature: 435 °C

Upper flammability or explosive limit, (Vol %): 13.000 % Lower flammability or explosive limit, (Vol %): 1.300 %

Explosive properties: Not applicable



Version: 1

Revision Date: 23.09.2020

Oxidising properties: Not applicable Decomposition temperature: / Solubility in water: Not soluble

Partition coefficient: noctanol/water: Not applicable

Odour: characteristic

Odour threshold: Not applicable Dynamic viscosity, 20°C: 400 mPa.s Kinematic viscosity, 40°C: 374 mm²/s Evaporation rate (n-BuAc = 1): 0.010

9.2 Other information:

Volatile organic component (VOC): 25.00 % Volatile organic component (VOC): 192.600 g/l

Sustained combustion test:/

SECTION 10: Stability and reactivity

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected



Version:

Revision Date: 23.09.2020

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

H302 Acute tox. 4: Harmful if swallowed.

H314 Skin Corr. 1B: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction. H341 Muta. 2: Suspected of causing genetic defects.

Calculated acute toxicity, ATE oral: 1 704.411 mg/kg

Calculated acute toxicity, ATE dermal: /

Isophoronediamine	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	1 030 mg/kg 1 100 mg/kg ≥ 50 mg/l
Benzyl alcohol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	1 620 mg/kg ≥ 5 000 mg/kg 11 mg/l
m-phenylenebis(methylamine)	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	1 180 mg/kg 3 100 mg/kg 11 mg/l
2,4,6-Tris(dimethyl amino methyl)phenol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	2 169 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Phenol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	340 mg/kg 660 mg/kg 3 mg/l

SECTION 12: Ecological information

12.1 Toxicity:

Isophoronediamine	EC50 (Algae):	12 mg/L (Scenedesmus)(72h)
		3 - (/ /



Version: 1

Revision Date: 23.09.2020

Benzyl alcohol	LC50 (Fish):	460 mg/L (72h)	
	EC50 (Daphnia):	230 mg/L (48h)	
	NOEC (Daphnia):	310 mg/L (72h)	
	EC50 (Algae):	770 mg/L (72h)	
m-phenylenebis(methylamine)	LC50 (Fish):	87.6 mg/L (96h)	
	EC50 (Daphnia):	87.6 mg/L (96h)	
	EC50 (Algae):	20.3 mg/L (72h)	
	EC50 (soil microorgan	nisms): > 1000 mg/L (30min)	
2,4,6-Tris(dimethyl amino methyl)phenol	EC50 (Algae):	84 mg/L (72h)	
Phenol	LC50 (Fish):	21.93 mg/L (14d)	
	NOEC (Fish):	4 mg/L (14d)	
	EC50 (Daphnia):	3.1 mg/L (48h)	
	EC50 (Algae):	61.1 mg/L (96h)	

12.2 Persistence and degradability:

No additional data available

12.3 Bioaccumulative potential:

No additional data available

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 1 Solubility in water: Not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.





Version:

Revision Date: 23.09.2020

SECTION 14: Transport information

14.1 UN number:

2735

14.2 UN proper shipping name:

UN 2735 Amines, liquid, corrosive, n.o.s. (mixture with Isophoronediamine; m-phenylenebis(methylamine)), 8, III, (E)

14.3 Transport hazard class(es):

Class(es): 8

Identification number of the hazard: 80

14.4 Packing group:

Ш

14.5 Environmental hazards:

Not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: Risk of burns. Risk to the aquatic environment and the sewerage system. Additional guidance:



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1



Version: 1

Revision Date: 23.09.2020

Volatile organic component (VOC): 25.000 % Volatile organic component (VOC): 192.600 g/l Composition by regulation (EC) 648/2004: None

15.2 Chemical Safety Assessment:

No data available

SECTION 16: Other information

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE: Acute Toxicity Estimate BCF: Bioconcentration factor CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

LD50: median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative

TLV: Threshold Limit Value

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

WGK 1: Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

H301 Acute tox. 3: Toxic if swallowed. H302 Acute tox. 4: Harmful if swallowed.

H302+H312 Acute tox. 4: Harmful if swallowed or in contact with skin.

H311 Acute tox. 3: Toxic in contact with skin.

H319 Eye Irrit. 2: Causes serious eye irritation.

H314 Skin Corr. 1B: Causes severe skin burns and eye damage.

H314 Skin Corr. 1C: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction.

H331 Acute tox. 3: Toxic if inhaled.

H332 Acute tox. 4: Harmful if inhaled.

H341 Muta. 2: Suspected of causing genetic defects.

H373 STOT RE 2: May cause damage to organs through prolonged or repeated exposure.

H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Safety Data Sheet According to Regulation (EC) No. 1907/2006



Trade Name: EUCOREP EP - B

Version: 1

Revision Date: 23.09.2020

CLP Calculation method: Calculation method

Reason of revision, changes of following items: Section: 11

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application , the user must carry out a material suitability and safety study himself.