

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 30/04/2015

Revision date: 15/01/2016

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: MIXTANE ROLLER
Product group	: Paint

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Libert Paints nv.
Langerbruggekaai 6
9000 Gent - BELGIUM
T 00 32 9 216 88 70 - F 00 32 9 226 61 81
MSDS@Libertpaints.com

1.4. Emergency telephone number

Emergency number : 070/245.245 (B)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
--------------	------

Skin Irrit. 2	H315
---------------	------

Eye Irrit. 2	H319
--------------	------

STOT RE 2 H373

Aquatic Chronic 3 H412

Full text of H-statements: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07



GHS08

Signal word (CLP) : Warning

Hazard statements (CLP)	: H226 - Flammable liquid and vapour H315 - Causes skin irritation H319 - Causes serious eye irritation H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects
-------------------------	---

Precautionary statements (CLP)

- : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- P271 - Use only outdoors or in a well-ventilated area
- P280 - Wear protective gloves. Contact your supplier to choose the most suitable protective gloves.
- P302+P352 - IF ON SKIN: Wash with plenty of soap and water
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P314 - Get medical advice/attention if you feel unwell

EUH-statements	: EUH208 - Contains GLYCEROL ESTER WITH A SYNTH. FATTY ACID CONTAINING 10 CARBON, reaction mass of .alpha.-3-(3-(2H- benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-.omega.-hydroxypoly(oxyethylene) and .alpha.- 3-(3-(2H-benzotriazol-2-yl)-5- tert-butyl-4-hydroxyphenyl)propionyl-.omega.-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene), Reaction mass of bis(1,2,2,6,6-pentamethyl-4-
----------------	--

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	15 - 20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
N-BUTYL ACETATE	(CAS No) 123-86-4 (EC no) 204-658-1 (EC index no) 607-025-00-1 (REACH-no) 01-2119485493-29	5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
HYDROCARBONS, C9, aromatics	(CAS No) 64742-95-6 (EC no) 265-199-0 (EC index no) 649-356-00-4 (REACH-no) 01-2119455851-35	5 - 10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-METHOXY-1-METHYLETHYL ACETATE substance with a Community workplace exposure limit	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 (REACH-no) 01-2119475791-29	5 - 10	Flam. Liq. 3, H226
ETHYLBENZENE	(CAS No) 100-41-4 (EC index no) 601-023-00-4 (REACH-no) 01-2119489370-35	2,5 - 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
reaction mass of .alpha.-3-(3-(2H- benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyl-.omega.-hydroxypoly(oxyethylene) and .alpha.- 3-(3-(2H-benzotriazol-2-yl)-5- tert-butyl-4-hydroxyphenyl)propionyl-.omega.-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	(EC index no) 607-176-00-3 (REACH-no) 01-0000015075-76	< 1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(REACH-no) 01-2119491304-40	< 1	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
GLYCEROL ESTER WITH A SYNTH. FATTY ACID CONTAINING 10 CARBON	(CAS No) 26761-45-5 (EC no) 247-979-2 (REACH-no) 01-2119431597-33	< 1	Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
-------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Carbon dioxide. Dry powder.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : The spill should be cleaned up by a trained cleaning personnel, wearing respiratory and eye protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage with non-combustible absorbent material and transfer in container for disposal according to local/national regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid unnecessary exposure. Immediately remove product. No open flames. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a well-ventilated place. When not in use, keep the container closed. Keep in fireproof place.
Incompatible materials : Heat sources. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylene (1330-20-7)		
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
ETHYLBENZENE (100-41-4)		
EU	IOELV TWA (mg/m ³)	442 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	884 mg/m ³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
EU	IOELV TWA (mg/m ³)	275 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	550 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

8.2. Exposure controls

Personal protective equipment	: Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.
Hand protection	: Wear protective gloves. Contact your supplier to choose the most suitable protective gloves.
Eye protection	: Safety glasses
Respiratory protection	: Wear appropriate mask



Environmental exposure controls	: Try to avoid the material runs off in drains or watercourse. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers, lakes or drains inform the respective authorities.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 25 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,05
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 500
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

In use may form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight.

10.5. Incompatible materials

No additional information available

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Xylene (1330-20-7)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (mg/l)	17,2 mg/l/4h
N-BUTYL ACETATE (123-86-4)	
LD50 oral rat	14 g/kg
LD50 oral	7,4 g/kg
LC50 inhalation rat (mg/l)	> 2000 mg/kg
HYDROCARBONS, C9, aromatics (64742-95-6)	
LD50 oral rat	3592 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	> 6193 mg/l/4h
GLYCEROL ESTER WITH A SYNTH. FATTY ACID CONTAINING 10 CARBON (26761-45-5)	
LD50 oral rat	9600 mg/kg
LD50 dermal rabbit	3800 mg/kg
LC50 inhalation rat (mg/l)	240 mg/m ³
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 23,8 mg/l 6u
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure .
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Xylene (1330-20-7)	
LC50 fish 1	13,5 mg/l 96u
EC50 Daphnia 1	3,82 mg/l 48u
ETHYLBENZENE (100-41-4)	
LC50 fish 1	4,2 mg/l 96u
EC50 Daphnia 1	1,8 mg/l 48u
EC50 other aquatic organisms 1	12 mg/l
ErC50 (algae)	4,6 mg/l 72u
N-BUTYL ACETATE (123-86-4)	
EC50 Daphnia 1	44 mg/l 48u
EC50 other aquatic organisms 1	647,7 mg/l 72u
HYDROCARBONS, C9, aromatics (64742-95-6)	
LC50 fish 1	9,22 mg/l 96u

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

HYDROCARBONS, C9, aromatics (64742-95-6)	
EC50 Daphnia 1	6,14 mg/l 48u
EC50 other aquatic organisms 1	1 - 10 mg/l
ErC50 (algae)	19 mg/l 96u

GLYCEROL ESTER WITH A SYNTH. FATTY ACID CONTAINING 10 CARBON (26761-45-5)	
LC50 fish 1	5 mg/l 96u
EC50 Daphnia 1	4,8 mg/l 48u
EC50 other aquatic organisms 1	3,5 mg/l 96u

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
LC50 fish 1	> 100 mg/l 96u
EC50 Daphnia 1	> 500 mg/l 48u
ErC50 (algae)	> 1000 mg/l 72u

12.2. Persistence and degradability

MIXTANE ROLLER	
Persistence and degradability	Not established.
N-BUTYL ACETATE (123-86-4)	
Biodegradation	83 % 28d

12.3. Bioaccumulative potential

MIXTANE ROLLER	
Bioaccumulative potential	Not established.
Xylene (1330-20-7)	
Log Pow	3,15
ETHYLBENZENE (100-41-4)	
Log Pow	3,118

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to a special collecting point in accordance with local legislation.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number	
UN-No. (ADR)	: 1263
UN-No. (IMDG)	: 1263
UN-No. (IATA)	: 1263
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name	
Proper Shipping Name (ADR)	: PAINT / PAINT RELATED MATERIAL
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (IATA)	: Paint
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable
Transport document description (ADR)	: UN 1263 PAINT / PAINT RELATED MATERIAL, 3, III, (D/E)
Transport document description (IMDG)	: UN 1263 PAINT, 3, III

14.3. Transport hazard class(es)	
ADR	
Transport hazard class(es) (ADR)	: 3

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Danger labels (ADR) : 3

:



IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3

:



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3

:



ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 163, 640F, 650

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, LP01, R001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T2

Portable tank and bulk container special provisions (ADR) : TP1, TP29

Tank code (ADR) : L4BN

Vehicle for tank carriage : FL

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Transport category (ADR) : 3
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E

- Transport by sea

Special provisions (IMDG) : 163, 223, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

- Inland waterway transport

Not subject to ADN : No

- Rail transport

Carriage prohibited (RID) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : 500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

MIXTANE ROLLER

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
Skin Sens. 1A	Sensitisation — Skin, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction

SDS EU (REACH Annex II)

The information contained in each data sheet is based on the data available to us at this time, and is believed to be accurate based upon that data. It is provided independently of any sale of the product, for purpose of hazard communication. It is not intended to constitute product performance information, and no express or implied warranty of any kind is made with respect to the product, underlying data or the information contained herein. You are urged to obtain data sheets for all products you buy, process, use or distribute, and are encouraged to advise those who may come in contact with such products of the information contained herein. This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Libert paints nv.sa. to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.