

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Paracol Universal Flooring

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

DL CHEMICALS  
Roterijstraat 201-203  
B-8793 Waregem - Belgium  
T + 32 56 62 70 51 - F + 32 56 60 95 68  
[info@dl-chem.com](mailto:info@dl-chem.com) - [www.dl-chem.com](http://www.dl-chem.com)

#### 1.4. Emergency telephone number

Emergency number : + 32 70 245 245

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]  
Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1);. May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
gemodificeerde hars esters	(CAS-No.) 8050-15-5 (EC-No.) 232-476-2 (REACH-no) 01-2119969275-26	< 25	Aquatic Chronic 3, H412

# Paracol Universal Flooring

## Safety Data Sheet

according to Regulation (EU) 2015/830

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Move to fresh air.
First-aid measures after skin contact	: Wash skin with mild soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a specialist.
First-aid measures after ingestion	: Rinse mouth.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard. Not combustible.

#### 5.3. Advice for firefighters

Precautionary measures fire	: Evacuate unnecessary personnel. Do not breathe fumes from fires or vapours from decomposition. Exercise caution when fighting any chemical fire.
Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Wear a self contained breathing apparatus.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : [In case of inadequate ventilation] wear respiratory protection. Equip cleanup crew with proper protection.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Shovel or sweep up and put in a closed container for disposal.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure.
Handling temperature	: 5 - 30 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

# Paracol Universal Flooring

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, well-ventilated area.  
Maximum storage period : 12 months  
Storage temperature : 5 - 25 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

1.2-Propyleenglycol (57-55-6)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	474 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	150 ppm

### 8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Gloves. Safety glasses.

Hand protection:

Time of penetration is to be checked with the glove producer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,1		EN ISO 374

Eye protection:

Type	Use	Characteristics	Standard
Safety glasses		With side shields	EN 166

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation



Consumer exposure controls:

Avoid contact with skin and eyes. Take off immediately all contaminated clothing. Wash hands and other exposed areas with soap and water before leaving work.

Other information:

Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Pasty.  
Colour : Off-white.  
Odour : characteristic.  
Odour threshold : No data available  
pH : 7,5

# Paracol Universal Flooring

## Safety Data Sheet

according to Regulation (EU) 2015/830

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,22 g/ml
Solubility	: Water: Soluble
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

1.2-Propyleenglycol (57-55-6)	
LD50 oral rat	> 20000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 317 mg/l
Calcium/ Magnesium Carbonate (16389-88-1)	
LD50 oral rat	> 5000 mg/kg
gemodificeerde hars esters (8050-15-5)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

# Paracol Universal Flooring

## Safety Data Sheet

according to Regulation (EU) 2015/830

Skin corrosion/irritation	: Not classified pH: 7,5
Serious eye damage/irritation	: Not classified pH: 7,5
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

1.2-Propyleenglycol (57-55-6)	
LC50 fish 1	51400 mg/l (OECD 203 method)
LC50 fish 2	40613 mg/l Salmo gairdneri
EC50 Daphnia 1	18340 mg/l Ceriodaphnia Dubia
EC50 96h algae (1)	19000 mg/l Pseudokirchneriella subcapitata
ErC50 (algae)	24200 mg/l (OECD 201 method)

  

gemodificeerde hars esters (8050-15-5)	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	27 mg/l
EC50 72h algae (1)	> 1000 mg/l
NOEC chronic fish	> 1000 mg/l

#### 12.2. Persistence and degradability

1.2-Propyleenglycol (57-55-6)	
Persistence and degradability	Readily biodegradable.
Biodegradation	81 % 28 days

  

gemodificeerde hars esters (8050-15-5)	
BOD (% of ThOD)	54 % ThOD 28 days

#### 12.3. Bioaccumulative potential

1.2-Propyleenglycol (57-55-6)	
Bioconcentration factor (BCF REACH)	0,09
Log Pow	-1,07
Bioaccumulative potential	not bioaccumulable.

  

gemodificeerde hars esters (8050-15-5)	
Bioaccumulative potential	Not determined.

#### 12.4. Mobility in soil

1.2-Propyleenglycol (57-55-6)	
Surface tension	71,6 mN/m at 21,5°C

#### 12.5. Results of PBT and vPvB assessment

Paracol Universal Flooring	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

# Paracol Universal Flooring

## Safety Data Sheet

according to Regulation (EU) 2015/830

Component	
1.2-Propyleenglycol (57-55-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
gemodificeerde hars esters (8050-15-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Reprocess or burn in an approved incinerator.
Product/Packaging disposal recommendations	: Empty the packaging completely prior to disposal. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
European List of Waste (LoW) code	: 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

## SECTION 14: Transport information

In accordance with ADR

ADR	
14.1. UN number	Not applicable
14.2. UN proper shipping name	Not applicable
14.3. Transport hazard class(es)	Not applicable
14.4. Packing group	Not applicable
14.5. Environmental hazards	Not applicable
No supplementary information available	

### 14.6. Special precautions for user

- Overland transport  
Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
-------------------	---

# Paracol Universal Flooring

## Safety Data Sheet

according to Regulation (EU) 2015/830

H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); . May produce an allergic reaction.
EUH210	Safety data sheet available on request.

MSDS Reach Annex II DL-Chem

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.