

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Parafoam 1K
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

DL CHEMICALS
Roterijstraat 201-203
B-8793 Waregem - Belgium
T + 32 56 62 70 51 - F + 32 56 60 95 68
info@dl-chem.com - www.dl-chem.com

1.4. Emergency telephone number

Emergency number : + 32 70 245 245

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222; H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Reproductive toxicity, Additional category, Effects on or via lactation	H362
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 4	H413

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



CLP Signal word

: Danger

Hazardous ingredients

: 4,4'-methylenediphenyl diisocyanate, isomers and homologues; alkanes, C14-17, chloro

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.
H362 - May cause harm to breast-fed children.
H373 - May cause damage to organs through prolonged or repeated exposure.
H413 - May cause long lasting harmful effects to aquatic life.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH204 - Contains isocyanates. May produce an allergic reaction.

Extra phrases

: Persons already sensitised to diisocyanates may develop allergic reactions when using this product
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

2.3. Other hazards

No additional information available

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
4,4'-methylenediphenyl diisocyanate, isomers and homologues	(CAS-No.) 9016-87-9 (EC-No.) 618-498-9	40 - <60	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
isobutane (Note C)(Note U)	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119485395-27	10 - <20	Flam. Gas 1, H220 Press. Gas (Comp.), H280
alkanes, C14-17, chloro, chlorinated paraffins, C14-17	(CAS-No.) 85535-85-9 (EC-No.) 287-477-0 (EC Index-No.) 602-095-00-X (REACH-no) 01-2119519269-33	10 - <20	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Propane-1,2-diol, propoxylated	(CAS-No.) 25322-69-4 (EC-No.) 500-039-8 (REACH-no) 01-2119493630-37	10 - <20	Acute Tox. 4 (Oral), H302
dimethyl ether (Note U)	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8 (REACH-no) 01-2119472128-37	2,5 - <5	Flam. Gas 1, H220 Press. Gas (Comp.), H280
propane (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	2,5 - <5	Flam. Gas 1, H220 Press. Gas (Comp.), H280

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U : When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Take victim to fresh air, in a quiet place in an half laying position, do artificial respiration if necessary and urgently take medical advice.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If necessary seek medical advice.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice (show the label where possible).
First-aid measures after ingestion	: Do not induce vomiting. Vomiting: prevent asphyxia/aspiration pneumonia. Keep at rest. Rinse mouth out with water.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : ABC-powder. Alcohol resistant foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use water.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes.

5.3. Advice for firefighters

Firefighting instructions : Cool down the containers exposed to heat with a water spray.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
Other information : Prevent fire fighting water from entering the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip rescue crew with proper protection. Equip cleanup crew with proper protection.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Do not absorb in saw-dust or other combustible absorbents.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep container tight closed.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place.
Heat and ignition sources : Store away from direct sunlight or other heat sources.
Storage area : Keep away from food and drink.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dimethyl ether (115-10-6)		
EU	IOELV TWA (mg/m ³)	1920 mg/m ³
EU	IOELV TWA (ppm)	1000 ppm
United Kingdom	WEL TWA (mg/m ³)	400 mg/m ³
United Kingdom	WEL TWA (ppm)	766 ppm
United Kingdom	WEL STEL (mg/m ³)	958 mg/m ³
United Kingdom	WEL STEL (ppm)	500 ppm

8.2. Exposure controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment:

Face shield.

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hand protection:

Time of penetration is to be checked with the glove producer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves					EN 374-1, EN 374-3, EN 420

Eye protection:

Type	Use	Characteristics	Standard
Face shield	Droplet		EN 166, EN 167, EN 168

Skin and body protection:

Type	Standard
Wear anti-static discharges clothing and shoes. Foresee ground with earth	EN 1149-1, EN 1149-2, EN 1149-3, EN 13034, EN ISO 13982-1, EN ISO 6529, EN ISO 6530, EN 464

Respiratory protection:

Device	Filter type	Condition	Standard
Gas mask	Gas filters, Particle filter		EN 149, EN 405



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Aerosol
Boiling point	: -12 °C Aerosol propellant
Flash point	: -83 °C Aerosol propellant
Auto-ignition temperature	: 460 °C Aerosol propellant
Vapour pressure	: < 300 kPa
Relative density	: 0,99

9.2. Other information

VOC content	: 19,53 %
-------------	-----------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Direct sunlight.

10.5. Incompatible materials

Strong acids, strong bases and oxidation agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Organic compounds.

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Additional information	: Danger of serious damage to health by prolonged exposure through inhalation

4,4'-methylenediphenyl diisocyanate, isomers and homologues (9016-87-9)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 9400 mg/kg
LC50 inhalation rat (mg/l)	11 mg/l/4h
alkanes, C14-17, chloro, chlorinated paraffins, C14-17 (85535-85-9)	
LD50 oral rat	4000 mg/kg (IUCLID)
LD50 dermal rat	4000 mg/kg
LC50 inhalation rat (mg/l)	1h 48170
Propane-1,2-diol, propoxylated (25322-69-4)	
LD50 oral rat	2150 mg/kg
LD50 dermal rabbit	20100 mg/kg
isobutane (75-28-5)	
LC50 inhalation rat (ppm)	570000 ppm IUCLID
dimethyl ether (115-10-6)	
LD50 oral	> 2000 mg/kg
LD50 dermal	> 2000 mg/kg
LC50 inhalation rat (mg/l)	308,5 mg/l
propane (74-98-6)	
LC50 inhalation rat (mg/l)	658 mg/l

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: May cause harm to breast-fed children.
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

Parafoam 1K	
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: May cause long lasting harmful effects to aquatic life.

Parafoam 1K	
EC50 Daphnia 1	1000 mg/l
EC50 72h algae (1)	1000 mg/l
4,4'-methylenediphenyl diisocyanate, isomers and homologues (9016-87-9)	
LC50 fish 1	96h 1000 mg/l (OECD 203 method)
EC50 Daphnia 1	24h 1000 mg/l (OECD 202 method)
EC50 other aquatic organisms 2	3h 100 mg/l Bacteria
ErC50 (algae)	72h 1640 mg/l (OECD 201 method)
NOEC (chronic)	112d 10000 mg/l Daphnia magna (Big water flea)
NOEC chronic fish	112d > 10000 mg/l
NOEC chronic crustacea	21d > 10 mg/l Daphnia magna (Big water flea)
NOEC chronic algae	112d > 10000 mg/l

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propane-1,2-diol, propoxylated (25322-69-4)	
LC50 fish 1	650 - 1700 mg/l
alkanes, C14-17, chloro, chlorinated paraffins, C14-17 (85535-85-9)	
LC50 fish 1	5000 mg/l Alburnus alburnus (alburnum)
EC50 Daphnia 1	5,9 µg/l Daphnia magna (Big water flea) M = 100
EC50 72h algae (1)	> 3,2 mg/l
NOEC chronic fish	14d > 125 Alburnus alburnus (alburnum)
dimethyl ether (115-10-6)	
NOEC (acute)	48 h 4000 mg/l Daphnia Magna
NOEC (chronic)	96 h 4000 mg/l Poecilia reticulata

12.2. Persistence and degradability

4,4'-methylenediphenyl diisocyanate, isomers and homologues (9016-87-9)	
Persistence and degradability	Not easily bio-degradable (according to OECD-criteria).
Biodegradation	28d 0 %

12.3. Bioaccumulative potential

4,4'-methylenediphenyl diisocyanate, isomers and homologues (9016-87-9)	
Bioconcentration factor (BCF REACH)	200
Bioaccumulative potential	highly bioaccumulative.
alkanes, C14-17, chloro, chlorinated paraffins, C14-17 (85535-85-9)	
Log Pow	5,47 - 8,01
isobutane (75-28-5)	
Bioconcentration factor (BCF REACH)	27
Log Pow	2,76
Bioaccumulative potential	Low bioaccumulation potential.
propane (74-98-6)	
Bioconcentration factor (BCF REACH)	13
Log Pow	2,86
Bioaccumulative potential	Low bioaccumulation potential.

12.4. Mobility in soil

isobutane (75-28-5)	
Log Koc	35
Ecology - soil	Very mobile.
dimethyl ether (115-10-6)	
Surface tension	0,001136 N/m
propane (74-98-6)	
Log Koc	460
Ecology - soil	medium.

12.5. Results of PBT and vPvB assessment

Component	
alkanes, C14-17, chloro, chlorinated paraffins, C14-17 (85535-85-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830


SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Handle uncleaned empty containers as full ones.
European List of Waste (LoW) code	: 16 05 04* - gases in pressure containers (including halons) containing dangerous substances
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none">— flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and 75 °C;— flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;— flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;— flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;— water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;— other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence

SECTION 14: Transport information

In accordance with ADR

ADR	
14.1. UN number	1950
14.2. UN proper shipping name	AEROSOLS
	UN 1950 AEROSOLS, 2.1, (D)
14.3. Transport hazard class(es)	2.1
	
14.4. Packing group	Not applicable
14.5. Environmental hazards	Dangerous for the environment : No
No supplementary information available	

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	4,4'-methylenediphenyl diisocyanate, isomers and homologues - alkanes, C14-17, chloro, chlorinated paraffins, C14-17
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	4,4'-methylenediphenyl diisocyanate, isomers and homologues
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	alkanes, C14-17, chloro, chlorinated paraffins, C14-17
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	isobutane - propane - dimethyl ether

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 19,53 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

Parafoam 1K

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH204	Contains isocyanates. May produce an allergic reaction.

MSDS Reach Annex II DL-Chem

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product