

EUCOFLOOR NET

CLEANING PRODUCT FOR SYNTHETIC RESIN SYSTEMS

FIELD OF APPLICATION

EUCOFLOOR NET is a product based on concentrated surfactants intended for the thorough cleaning of synthetic resin floors as well as for their routine maintenance.

- Routine maintenance of cast floors.
- Thorough cleaning of heavily soiled areas.
- Removal of tire marks on parking floors.
- All surfaces covered with a synthetic resin system, but also tiles, flexible synthetic coating, ...

BENEFITS & FEATURES

- Odourless
- Adjusted dilution percentage depending on the degree of pollution.

APPLICATION

Application conditions

The recommended application temperature is between +5°C and +35°C..

Tools & complementary products

- Clean mixing containers.
- Pure water.
- Cleaning equipment.

Preparations

Clean the surface of dust and other loose impurities by brushing. Make sure the surface is dry and free from free standing water. First dilute EUCOFLOOR NET according to:

Highly polluted areas:
1 part of EUCOFLOOR NET + 1 part of water.

Routine maintenance:
1 part of EUCOFLOOR NET + 10 to 20 parts of water, according to the degree of pollution.

Application of the product

EUCOFLOOR NET can be used with all cleaning equipment commonly used for cleaning floors (rubber squeegee, brush, scrubber drier, etc...) Rinse the surface excessively with clean water after each cleaning.

Finishing

Since EUCOFLOOR NET has a strong cleaning power, a slight loss of gloss may occur with certain resins. To solve this problem, we recommend applying a wax for synthetic resin floors.

Cleaning of the tools

Rinse thoroughly with clean water.

TECHNICAL DATA

Consumption

Depending on the degree of pollution. See also "preparation" described above.

Technical data & reaction times

Property	Value
Basic raw materials	Concentrated surfactants
Density (20°C)	0.97 kg/dm ³
pH	12,5 (strong alkaline cleaning agent)
Colour - View	Bluish liquid
Odour	Odourless

Additional documentation & referrals

Always consult all technical data sheets and material safety data sheets of the products to be used. Always work with clean tools in good condition.

APPEARANCE - COMPOSITION - PACKAGING

EUCOFLOOR NET is available as follows: 20 L tin.
Storage takes place in a dry room, in the original and unopened packaging between +5°C and +30°C; shelf life 12 months if stored under the conditions described above.

ADDITIONAL COMMENTS

For special applications it is advisable to consult your EUCCHEM BV representative.

SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at [op www.eucochem.com](http://op.www.eucochem.com). When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCCHEM bv cannot be held responsible on the basis of what is mentioned above. Should EUCCHEM bv nevertheless be held responsible for damage incurred, the claim will always be limited to the value of the necessary EUCCHEM bv products to be delivered in order to carry out a minimal repair. EUCCHEM bv strives to deliver products of consistent, good quality. All values on the technical data sheet are average values and are the result of tests performed under laboratory conditions. Values that are measured in jobsite conditions and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCCHEM bv products for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCCHEM bv products it is necessary to draw up a construction site log and to fill it in on a regular basis. EUCCHEM bv can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations set by EUCCHEM bv. We also refer to our general terms and conditions in case of dispute. This version of the technical data sheet replaces all previous versions. Version 1.0 Date: 14 October 2021 11:03 am