EUCOGRAN 0.1 - 0.3

FILLER FOR EUCOCHEM SYNTHETIC RESIN SYSTEMS.

FIELD OF APPLICATION

EUCOGRAN 0,1-0,3 is a mineral filler for EUCOCHEM synthetic resin systems.

- As a filler for primers.
- As a filler to make an egaliser or levelling layer with a binder.
- As a filler for multilayer synthetic resin floor systems.
- As a filler for self-levelling synthetic resin systems.

APPLICATION

See technical data sheet of the synthetic resin system to be used.

MAINTENANCE AFTER APPLICATION

See technical data sheet of the synthetic resin system to be used.

TECHNICAL DATA

Consumption

See technical data sheet of the synthetic resin system to be used.

Technical data

Property	Value
Basic raw materials	Silicium dioxyde (SiO_2) > 96%
Density	2,65 kg/dm^3
Aspect	Composite filler based on quartz sand
Colour	Light sand-coloured

Granulometry

Granulometry (µm)	Percentage
125-100	3.3%
160-125	11.0%
200-160	22.4%
250-200	36.7%
315-250	22.3%
400-315	4.0%
500-400	0.3%

Additional documentation & referrals

Always work with clean tools in good condition.

APPEARANCE - COMPOSITION - PACKAGING

EUCOGRAN 0.1- 0.3 is available in 25 kg bags.

EUCOGRAN 0.1- 0.3 be stored in its original, unopened packaging and in a dry room. Do not store in direct sunlight and between +10°C and +30°C. It has a shelf life of 12 months after production date, provided it is stored under the conditions described above.

ADDITIONAL COMMENTS

For special applications it is advisable to consult your EUCOCHEM BV representative.

SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at op www.eucochem.com. When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCOCHEM bv bv cannot be held responsible on the basis of what is mentioned above. Should EUCOCHEM bv nevertheless be held responsible for damage incurred, the claim will always be limited to the value of the necessary EUCOCHEM bv products to be delivered in order to carry out a minimal repair. EUCOCHEM bv strives to deliver products of consistent, good quality. All values on the technical data sheet are average values and are the result of tests performed under laboratory conditions. Values that are measured in jobsite conditions and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCOCHEM bv products for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCOCHEM bv products it is necessary to draw up a construction site log and to fill it in on a regular basis. EUCOCHEM bv can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations set by EUCOCHEM bv. We also refer to our general terms and conditions in case of dispute. This version of the technical data sheet replaces all previous versions. Version 1.0 Date: 14 October 2021 11:03 am

EUCOCHEM bv | Esperantolaan 13/7 | 3300 Tienen | België | office@eucochem.com | www.eucochem.com | Tel.+32 16 81 11 52