EUCOGRANMGB

MICRO GLASS BEADS AS FILLER TO MAKE EUCOCHEM COATINGS, PAINTS AND TOPCOATS ANTI SLIP

FIELD OF APPLICATION

EUCOGRAN MGB is a micro glass beads based filler to make EUCOCHEM coatings, paints and topcoats anti slip.

- Good mechanical resistance.
- · Good abrasion resistance.
- Does not collapse after mixing with the resin.
- Inert material.

APPLICATION

Application conditions

See the technical data sheet of the synthetic resin product.

Tools & complementary products

- · Mixer with spindle.
- · Clean mixing containers.

Application of the product

EUCOGRAN MGB must always be mixed into the resin with a mixer and spindle at low speed. For two component systems, EUCOGRAN MGB must always be mixed into the resin component before adding the hardener component.

TECHNICAL DATA

Consumption

Depending on the desired degree or roughness / anti slip: approx 2 to 5% on the total set weight of the synthetic resin product to be installed.

Technical data & reaction times

Property	Value
Basic raw materials	Massive micro glass beads
Aspect	Powder
Density	2.50 kg/dm ³
Colour	White

Chemical resistances

When used in applications with chemically products, it is advisable to consult your EUCOCHEM BV representative.

Additional documentation & referrals

Raadpleeg steeds alle technische fiches van de te gebruiken producten. Werk steeds met zuiver en in goede staat verkerend gereedschap.

APPEARANCE - COMPOSITION - PACKAGING

EUCOGRAN MGB is available in 20 kg bags.

EUCOGRAN MGB can be stored in its original, unopened packaging and in a dry room. Do not store in direct sunlight and between $+10^{\circ}$ C and $+30^{\circ}$ C. It has a shelf life of 12 months after production date, provided it is stored under the conditions described above.

ADDITIONAL COMMENTS

For special applications it is advisable to consult your EUCOCHEM BV representative.

SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at op www.eucochem.com. When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCOCHEM by by cannot be held responsible on the basis of what is mentioned above. Should EUCOCHEM by necessary EUCOCHEM by products and all this in the broadest sense, are necessary EUCOCHEM by products to be delivered in order to carry out a minimal repair. EUCOCHEM by strives to deliver din order to carry out a minimal repair. EUCOCHEM by strives to deliver din order to carry out a minimal repair. EUCOCHEM by strives and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCOCHEM by worducts for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCOCHEM by can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations are to guard to realise all previous versions. Version 1.0 Date: 14 October 2021 11:06 am

