

# EUCOPREV B GRID

## FIXING GRID FOR EUCOPREV B AND EUCOPREV B SALT BENTONITE SWELL STRIPS

### FIELD OF APPLICATION

EUCOPREV B GRID is a fixing grid for EUCOPREV B, EUCOPREV B SALT (BENTONITE swell strips).

- Mainly in vertical applications.
- Mainly in horizontal suspended applications.

### BENEFITS & FEATURES

- Strong.
- Good fixation of EUCOPREV B and EUCOPREV B SALT bentonite swelling strips.
- Easy to install.
- Nail with nail gun.

### APPLICATION

#### Application conditions

See technical data sheet of EUCOPREV B and EUCOPREV B SALT.

#### Tools & complementary products

- EUCOPREV B or EUCOPREV B SALT (to be ordered separately)
- Nail gun
- Nails (possibly with washers)

#### Preparations

EUCOPREV B GRID is a ready-made product.

#### Application of the product

Roll out EUCOPREV B or EUCOPREV B SALT in the centre of the joint and press the strip firmly against the surface. Place the EUCOPREV B GRID on the bentonite strip. Nail the bentonite strip together with the fixing net EUCOPREV B GRID in one operation against the substrate. Always use 4 nails with washer per meter. If the nail heads are too small in function of the mesh of EUCOPREV B GRID, washers can be used.

#### Finishing

After nailing the strip, the concrete can be poured immediately.

After combined gluing and nailing (see also the technical data sheets of EUCOPREV B, EUCOPREV B SALT and EUCOCOL MS) to fix the strips, it is necessary to wait before concreting until the EUCOCOL MS glue has hardened for 24 hours. Protect the installed strips against rain and water until the concrete is poured.

#### Cleaning of the tools

Does not apply.

### MAINTENANCE AFTER APPLICATION

Does not apply.

### TECHNICAL DATA

#### Consumption

Consumption depends on the total length of the construction joint to be treated. Take into account a minimum lateral overlap of 5 cm. 1 meter of grid per 1 meter of swelling strip.

### Technical data & reaction times

Property	Value
Basic raw materials	Galvanized steel
Shape	U shaped grid with mesh
Grid	Grid length = 1 meter long
Mesh dimensions	5 on 5 mm
Odour	Odourless

### Chemical resistances

Good chemical resistance.

### Additional documentation & referrals

Always consult all technical data sheets of the products to be used. Always work with clean tools in good condition.

### APPEARANCE - COMPOSITION - PACKAGING

#### EUCOPREV B GRID

U-shaped grid, 1 meter

Mesh of 5 on 5 mm.

30 x 1 m grids per box (= 30m per box)

72 boxes per pallet (= 2160 m per pallet)

Storage takes place in a dry room and in the unopened original packaging and has an indefinite shelf life if stored under the conditions described above.

EUCOPREV B GRID is non-toxic.

### ADDITIONAL COMMENTS

Does not apply For questions and special implementation conditions, contact EUCCHEM BV.

### SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at [www.eucochem.com](http://www.eucochem.com). When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCCHEM bv cannot be held responsible on the basis of what is mentioned above. Should EUCCHEM bv nevertheless be held responsible for damage incurred, the claim will always be limited to the value of the necessary EUCCHEM bv products to be delivered in order to carry out a minimal repair. EUCCHEM bv strives to deliver products of consistent, good quality. All values on the technical data sheet are average values and are the result of tests performed under laboratory conditions. Values that are measured in jobsite conditions and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCCHEM bv products for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCCHEM bv products it is necessary to draw up a construction site log and to fill it in on a regular basis. EUCCHEM bv can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations set by EUCCHEM bv. We also refer to our general terms and conditions in case of dispute. This version of the technical data sheet replaces all previous versions. Version 1.0 Date: 14 October 2021 11:07 am