

# EUCOPROOF CEM REACTIVE AGENT

## ADDITIVE FOR EUCOPROOF CEM REACTIVE

### FIELD OF APPLICATION

EUCOPROOF CEM REACTIVE AGENT is an aqueous, flexible rubber dispersion, based on a special latex. The material is compatible with all normal cements but the formulation has been specially developed for use as an additive for the EUCOPROOF CEM REACTIVE waterproofing slurry. EUCOPROOF CEM REACTIVE AGENT is used as a reactive additive of EUCOPROOF CEM REACTIVE and increases the water retention capacity of slurries. This protects the slurry against drying out too quickly. It also increases the flexibility of the entire waterproofing system. In addition, the bonding strength to the surface is improved and the slurry has a better processing consistency.

### BENEFITS & FEATURES

- Ready for addition to EUCOPROOF CEM REACTIVE
- Waterproof.
- Watery dispersion
- Increases wear resistance
- High solids content
- Improvement of the ability to retain water
- Solvent free
- Protection against drying too quickly
- Free from plasticizers
- Flexibility

### APPLICATION

#### Application conditions

See technical data sheet of EUCOPROOF CEM REACTIVE

#### Tools & complementary products

See technical data sheet of EUCOPROOF CEM REACTIVE

#### Preparations

See technical data sheet of EUCOPROOF CEM REACTIVE

#### Preparation of the product

Ready to use / for addition to EUCOPROOF CEM REACTIVE

#### Application of the product

See technical data sheet of EUCOPROOF CEM REACTIVE

#### Finishing

Does not apply.

#### Cleaning of the tools

Clean the used equipment with water. Remove cured product residues mechanically.

### MAINTENANCE AFTER APPLICATION

Does not apply.

### TECHNICAL DATA

#### Consumption

8 kg per 25 kg EUCOPROOF CEM REACTIVE

#### Technical data & reaction times

Property	Value
Basic raw materials	Rubber dispersion, additives
Bulk density	approx. 1,01 kg/dm <sup>3</sup>
Viscosity	approx. 90 mPas
pH	10
Solids content	> 10%
View - colour	White liquid

#### Chemical resistances

When used in applications with chemically contaminated water or chemical products, it is advisable to consult your EUCCHEM BV representative.

#### Additional documentation & referrals

Always consult all technical data sheets and material safety data sheets of the products to be used. Always work with clean tools in good condition.

### APPEARANCE - COMPOSITION - PACKAGING

EUCOPROOF CEM REACTIVE AGENT is available as follows:

8 kg can

Store EUCOPROOF CEM REACTIVE AGENT in a dry, frost-free room and in the unopened original packaging. Do not store in direct sunlight and between +5°C and +30°C. Shelf life 6 months after production date if kept under the above mentioned conditions.

### ADDITIONAL COMMENTS

For special applications it is advisable to consult your EUCCHEM BV representative.

### SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at [op www.eucochem.com](http://op.www.eucochem.com). When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCCHEM bv cannot be held responsible on the basis of what is mentioned above. Should EUCCHEM bv nevertheless be held responsible for damage incurred, the claim will always be limited to the value of the necessary EUCCHEM bv products to be delivered in order to carry out a minimal repair. EUCCHEM bv strives to deliver products of consistent, good quality. All values on the technical data sheet are average values and are the result of tests performed under laboratory conditions. Values that are measured in jobsite conditions and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCCHEM bv products for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCCHEM bv products it is necessary to draw up a construction site log and to fill it in on a regular basis. EUCCHEM bv can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations set by EUCCHEM bv. We also refer to our general terms and conditions in case of dispute. This version of the technical data sheet replaces all previous versions. Version 1.0 Date: 14 October 2021 11:10 am