

EUCOPROOF MB TAPE R

REPAIR TAPE, SPECIALLY COATED WITH GRANULES, HIGHLY ELASTIC

FIELD OF APPLICATION

EUCOPROOF MB TAPE R (Repair) a one-sided self-adhesive repair-tape. The tape consists of a highly flexible HDPE polymer film that is coated on both sides with special PSA-adhesive. The tape also has on one side an extra granular coating of silicon dioxide on one side, which result in extremely high adhesion to freshly poured concrete. The other side of the tape is protected with a silicon film, which must be removed immediately before application.

The tape is used for waterproofing basement walls, foundations, tunnels, floor slabs, etc. in combination with the EUCOPROOF MB membranes. The product is suitable for vertical and horizontal applications.

BENEFITS & FEATURES

- Highly flexible
- Pressure-sensitive adhesive
- Polymer film reinforced.
- Continuous thickness
- Larger contact surface due to granular structure (silicon dioxide)
- Adhesive side protection with film
- Waterproof against water under pressure
- Good chemical resistance
- UV resistant for > 30- 60 days
- Strong crack bridging
- High elongation
- Not harmful to ground water

APPLICATION

Application conditions

The recommended application temperature is between + 5°C and +40°C.

Tools & complementary products

- See technical data sheets of EUCOPROOF MB membranes.

Preparations

See technical data sheets of EUCOPROOF MB membranes.

Application of the product

See technical data sheets of EUCOPROOF MB membranes.

Finishing

See technical data sheets of EUCOPROOF MB membranes.

Cleaning of the tools

Does not apply.

MAINTENANCE AFTER APPLICATION

Does not apply.

TECHNICAL DATA

Consumption

1 m = 1 m

1 roll = 20 m

Technical data & reaction times

Base: Flexible polymer film

Coating adhesive side: Pressure sensitive polymer resin

Coating contact side: Granule, silicon dioxide

Colour White

Weight approx. 1 kg/m²

Thickness: approx. 1 mm

Length: 20 m

Width: 100 mm

Chemical resistances

Good chemical resistance. When used in applications with chemically polluted water, please contact EUCCHEM BV.

Additional documentation & referrals

Always consult all technical data sheets of the products to be used. Always work with clean tools in good condition.

APPEARANCE - COMPOSITION - PACKAGING

EUCOPROOF MB TAPE R is available as follows:

1 roll:

Length: 20 m

Width: 100 mm

EUCOPROOF MB TAPE R has a shelf life of 12 months in its original and closed packaging, if stored in a dry and frost free environment.

ADDITIONAL COMMENTS

For special applications it is advisable to consult EUCCHEM.

SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at www.eucochem.com. When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCCHEM bv cannot be held responsible on the basis of what is mentioned above. Should EUCCHEM bv nevertheless be held responsible for damage incurred, the claim will always be limited to the value of the necessary EUCCHEM bv products to be delivered in order to carry out a minimal repair. EUCCHEM bv strives to deliver products of consistent, good quality. All values on the technical data sheet are average values and are the result of tests performed under laboratory conditions. Values that are measured in jobsite conditions and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCCHEM bv products for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCCHEM bv products it is necessary to draw up a construction site log and to fill it in on a regular basis. EUCCHEM bv can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations set by EUCCHEM bv. We also refer to our general terms and conditions in case of dispute. This version of the technical data sheet replaces all previous versions. Version 1.0 Date: 14 October 2021 11:14 am