

EUCOSOLV PUMPCLEAN

ECOLOGICALLY RESPONSIBLE FLUSHING AGENT FOR INJECTION PUMPS

FIELD OF APPLICATION

EUCOSOLV PUMP CLEAN is a non-flammable solvent for cleaning and flushing polyurethane injection pumps and for cleaning used equipment. It consists of a composition of organic solvents with a high dissolving power of liquid polyurethane products.

- Flushing and cleaning of pumps and injections hoses used for injecting polyurethane injection resins.
- Cleaning of equipment that has been in contact with uncured polyurethane resins.

BENEFITS & FEATURES

- Ecologically responsible.
- Organic solvent.
- Non flammable.
- Does not contain water.

APPLICATION

Tools & complementary products

- Waste bucket or - barrel.

Equipment & complementary products

Flushing the pump before starting the injection:

Pour the flushing agent EUCOSOLV PUMP CLEAN into the reservoir of the pump and let it circulate for 3 to 4 minutes with the return open. Then completely remove the flushing agent from the pump in a waste bucket. When the flushing agent is completely out of the reservoir, the resin can be poured into the reservoir. When the injection hose no longer contains flushing agent, the injection with the resin can start.

Flushing the pump after use:

Empty the reservoir of the pump with the remaining injection resin. Pour the flushing agent EUCOSOLV PUMP CLEAN into the reservoir of the pump and let it circulate for 3 to 3 minutes with the return open. Then completely remove the flushing agent from the pump in a waste bucket. It is recommended to fill the pump and injection hose with some type of machine or vegetable oil when the pump is not used for a period longer than 1 working day.

TECHNICAL DATA

Consumption

Depending on the type of pump, the length of the injection hose and the type of contamination of the pump.

Technical data & reaction times

Property	Value
Basic raw materials	Organic solvents
Density	0.93 kg/dm ³
Flash point	196°C
Appearance	Clear, colourless liquid.
Odour	Typical

Chemical resistances

Attacks polyurethane and possibly other synthetic products.

Additional documentation & referrals

Always consult all technical data sheets and material safety data sheets of the products to be used. Always work with clean tools in good condition.

APPEARANCE - COMPOSITION - PACKAGING

EUCOSEAL PUMP CLEAN is available as follows:

5 kg can
20 kg can

Store EUCOSOLV PUMP CLEAN in a dry, well ventilated room and in the unopened original packaging. Do not store in direct sunlight and between +5°C and +30°C. EUCOSOLV PUMP CLEAN has an unlimited shelf life if kept under the above mentioned conditions.

ADDITIONAL COMMENTS

NEVER clean the injection pumps with water.

EUCOSOLV PUMP CLEAN can be reused several times depending on the degree of pollution of the pump.

SAFETY PRECAUTIONS

Always use personal protection in accordance with the local guidelines. Consult the appropriate safety sheets before use. All most recent safety data sheets are always available at www.eucochem.com. When in doubt, contact our technical service.

All information in this technical data sheet is provided in good faith and without any guarantees. The choice of a product for any application by the buyer or applicator, the processing of the products, the preparations, the finishing, the use of the right equipment to apply the products and all this in the broadest sense, are entirely beyond our control and are therefore entirely the responsibility of the buyer or applicator. Therefore, EUCCHEM bv cannot be held responsible on the basis of what is mentioned above. Should EUCCHEM bv nevertheless be held responsible for damage incurred, the claim will always be limited to the value of the necessary EUCCHEM bv products to be delivered in order to carry out a minimal repair. EUCCHEM bv strives to deliver products of consistent, good quality. All values on the technical data sheet are average values and are the result of tests performed under laboratory conditions. Values that are measured in jobsite conditions and the like may deviate from the stated values. This is because the environmental conditions, the application and the manner of processing our products are also outside our control. Please note that you should not add any products other than those indicated in our technical documentation. Only use EUCCHEM bv products for a system under construction. If you combine products from different suppliers or brands, the warranty expires irrevocably. When applying the EUCCHEM bv products it is necessary to draw up a construction site log and to fill it in on a regular basis. EUCCHEM bv can consult the construction site log at any time and / or request a copy to check whether the products and systems have been correctly installed or installed in accordance with the regulations set by EUCCHEM bv. We also refer to our general terms and conditions in case of dispute. This version of the technical data sheet replaces all previous versions. Version 1.0 Date: 14 October 2021 11:14 am