



## CHARACTERISTICS

- Ready to use, light finishing paste
- Can be applied in one single movement
- Does not sag or shrink
- Does not crack
- Is paintable after a few minutes, but ideal is after +/- 2 hours
- Can be abraded when dry (after 1 day) by abrasive paper
- Phthalate free

## APPLICATIONS

- For the filling of cracks, joints and gaps of max. 50 mm deep and 50 mm wide.
- Has an extremely strong adhesion on porous materials such as stone, concrete, plaster, wood, etc.
- Has to be painted twice when used outdoors.

TECHNICAL CHARACTERISTICS	
Type of sealant	Special acryl polymers
Consistency	Thixotropic paste
Density pot	0,45 g/ml
Open time	10 - 15 min
Possibility to abrase	After 1 day
Paintable	After a couple of minutes (ideal after +/- 2 h)
Shrinkage	Nil
Processing temperature	+5°C - +35°C
Shelf life, in the original packing in dry conditions between +5°C - +25°C	Min. 12 months
Temperature resistance	-20°C - +80°C.

PACKING AND COLOURS	
25 cartridges of 310 ml/box - 48 boxes/pallet	
White	
6 buckets of 1 l/box - 64 boxes/pallet	
White	
Bucket of 5 l - 60 buckets/pallet	
White	
Bucket of 10 l - 27 buckets/pallet	
White	

## METHOD OF USE

### Preparation

Apply the product on a clean and dry surface

### Application

- Bucket: Stir before use. Apply the product with a spatula and smooth afterwards. When too dry, add one coffee spoon of water for each 250 ml **Paracryl Parafill** and stir until a smooth paste is obtained.
- Cartridge: Use a spatula to apply the product and smoothen it.
- Layers of 4 to 25 mm give the best results.
- Max. 50 mm deep and 50 mm wide.
- Larger joints have to be filled in several steps with 1 day in between.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.

### Tooling

Finish with a wet spatula.

### Cleaning

Tools: With water before it is dry.

### Repairing

With the same product.

### SAFETY

Safety data sheet available on request.

### LIMITATIONS

Cannot be used on synthetic, metal and permanently humid surfaces.

### TECHNICAL APPROVALS



\* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).